



# THE SMART COMPANION

The successful skeye.pad range provides impressive high performance functionality and supports an exceedingly wide range of applications in the field service and logistics sector.



# TAILOR-MADE SOFTWARE TOOLS KEEP OPERATING AND DEVELOPMENT COSTS LOW

Its Marvell PXA255 CPU with 400 MHz and 128 RAM as well as 128 MB flash memory means that the skeye.pad also supports complex applications. Thanks to the operating system Windows CE 5.0 the versatile terminal can be easily integrated into existing IT infrastructures. The skeye.pad has a PCMCIA, CF and SD card slot, making it extremely flexible and additional periphery devices can be connected via USBand RS 232-ports. A broad range of tailor-made Skeye software tools simplify the creation of applications as well as the maintenance and care of the system and thus keeps the operating and development costs low.

#### SIMPLY EFFICIENT

The skeye dart is the ideal companion in many applications. The especially large 8.4" display is ideally suited for providing an above-average depiction of complex data and graphics, and makes the 900 g terminal an indispensable working tool boasting a particularly wide range of applications.

### **FLEXIBLE**

The skeye pad automotive is fitted permanently in the vehicle and optimally supports all modern applications in the logistics field. In addition, skeye pad automotive allows the user to connect a reversing camera, thus providing even greater safety in use.



## PRODUCT ACCESSORIES



skeye.pad XSL



Charging station



Desktop cradle



skeye.pad XSL with swivel head for fixed mounting in the vehicle



Car cradle



Pouch with belt clip

#### APPLICATIONS OVERVIEW

- Order management
- Data capture
- Warehouse logistics

#### FIELDS OF APPLICATIONS

- Field service
- Logistics
- Hospitality





#### **TECHNICAL DATA\***

#### System

- Marvell PXA255 CPU, 400 MHz
- 128 MB SD-RAM, 128 MB flash
- 213 mm (8,4") SVGA TFT, 800 x 600, touch screen
- Windows CE .NET 4.2 or Windows CE 5.0
- Silicon Motion graphics accelerator with 8 MB memory

#### **Communication options**

- WLAN IEEE® 802.11b/g (not in combination with SD slot)
  - Security: WPA2, WPA
  - Authentication: 802.1x
  - Encryption: AES, TKIP, WEP
  - Alternative: CF slot equipped with Summit SDC-CF10AG: IEEE® 802.11a/b/g
  - WiFi certified, CCX v4 compatible

#### Interfaces

- USB Host, USB Device
- RS232
- PCMCIA slot type II
- CF slot type II
- SD slot (not in combination with built-in WLAN)
- •

#### Auto ID options

- 1D laser scanner (opt.)
- •

#### Environment

- Operating temperature: -10 °C bis +50 °C
- •

#### Weight/dimensions

- ≈ 900 g
- 240 x 160 x 30 (L x W x H in mm)

#### Accessories

- Battery: 7,4 V/3600 mAh
- Desktop cradle incl. USB cable (Device)
- Replacement battery
- Battery charger (holds 1 battery)
- Car cradle:
  - Access for GPS mouse
  - 1 x RS 232, 1 x USB Host
  - Cigarette lighter connector with 5 A fuse
- Navigation software
  - Map & Guide Truck Navigator
  - skeye.guide
- Various cases

\* List of features inludes optional items

#### Höft & Wessel AG

Rotenburger Straße 20 30659 Hannover T +49 511 6102-0 F +49 511 6102-411 info@hoeft-wessel.com www.hoeft-wessel.com

#### Metric Group Ltd. UK

Metric House Westnead Industrial Estate Westlea, Swindon, SN5 7AD T +44 1793 647-800 F +44 1793 647-802 info@metricgroup.co.uk www.metricgroup.co.uk